







Compliant SDS for GHS: HazCom 2012 / United States; WHMIS 2015 / Canada

SAFETY DATA SHEET

: 11/01/2016

2

Date

Version

AMSOIL Heavy Duty Antifreeze/Coolant

Section 1. Identification

GHS product identifier

: AMSOIL Heavy Duty Antifreeze/Coolant

Code : ANTHD : Liquid.

Identified uses : Antifreeze.

Manufacturer : AMSOIL INC.

One AMSOIL Center Superior, WI 54880 Tel: +1 715-392-7101

Initial Supplier : AMSOIL INC.

(Canada)

Bordner, Ladner, Gervais
Scotia Plaza, 40 King St W
Toronto, ON, Canada M5H 3Y4

Tel: +1 416-367-6547

Emergency telephone

number (with hours of

operation)

: CHEMTREC: Within USA and Canada: 1-800-424-9300;

Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

(24/7)

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: ACUTE TOXICITY (oral) - Category 4 SKIN IRRITATION - Category 2 EYE IRRITATION - Category 2A

SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2

GHS label elements

Hazard pictograms





Signal word : Warning

Hazard statements : Harmful if swallowed.

Causes serious eye irritation.

Causes skin irritation.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

FREE CATALOG

SAVE UP TO 25%

AMSOIL Heavy Duty Antifreeze/Coolant

ANTHD

Prevention

: Wear protective gloves. Wear eye or face protection. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling.

Response

: Get medical attention if you feel unwell. IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell. Rinse mouth. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage

: Not applicable.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified (HNOC)

Physical hazards not otherwise classified

(PHNOC)

Health hazards not otherwise classified

(HHNOC)

: None known.

: None known.

Section 3. Composition/information on ingredients

Substance/mixture

Other means of identification

: Not available.

: Mixture

CAS number/other identifiers

CAS number : Not applicable.

Product code : ANTHD

Ingredient name	%	CAS number
Ethanediol Organic acids and other Proprietary Inhibitors	40 - 60 5 - 10	107-21-1 -

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Get medical attention.

BUY ONLINE

FREE CATALOG

SAVE UP TO 25%

AMSOIL Heavy Duty Antifreeze/Coolant

ANTHD

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 20 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact: Causes skin irritation.Ingestion: Harmful if swallowed.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No known significant effects or critical hazards.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion : No known significant effects or critical hazards.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

Protection of first-aiders: No action shall be taken involving any personal risk or without suitable training. It may

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

ANTHD

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous thermal decomposition products

 Decomposition products may include the following materials: carbon dioxide carbon monoxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

ANTHD

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Avoid contact with used product. Do not reuse container.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

United States

Ingredient name	Exposure limits
Ethanediol	ACGIH TLV (United States, 3/2016). C: 100 mg/m³ Form: Aerosol.

Canada

Occupational exposure limits

Ingredient name	Exposure limits
Ethanediol	CA Ontario Provincial (Canada, 7/2015). C: 100 mg/m³ Form: Aerosol only CA British Columbia Provincial (Canada, 5/2015). C: 100 mg/m³ Form: Aerosol. TWA: 10 mg/m³ 8 hours. Form: Particulate. STEL: 20 mg/m³ 15 minutes. Form: Particulate. C: 50 ppm Form: Vapour CA Saskatchewan Provincial (Canada, 7/2013). CEIL: 100 mg/m³ Form: Aerosol. CA Quebec Provincial (Canada, 1/2014). STEV: 50 ppm 15 minutes. Form: Vapor and mist STEV: 127 mg/m³ 15 minutes. Form: Vapor and mist CA Alberta Provincial (Canada, 4/2009). C: 100 mg/m³

BUY ONLINE

FREE CATALOG

SAVE UP TO 25%

AMSOIL Heavy Duty Antifreeze/Coolant

ANTHD

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

Physical state : Liquid.

Color : Red.

Odor : Sweet.

Odor threshold : Not available.

pH : 8 to 8.6

 Melting point
 : -36.667°C (-34°F)

 Boiling point
 : 107.78°C (226°F)

Flash point : Closed cup: 116°C (241°F) [Pensky-Martens.]

Evaporation rate : Not available.

AMSOIL Heavy Duty Antifreeze/Coolant

ANTHD

Flammability (solid, gas) : Not available.

Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure

: 1.3 kPa (10 mm Hg) at 20 °C

Vapor density : 2.1 [Air = 1]

Relative density : 1.03 to 1.08

Solubility : Soluble.

Partition coefficient: n- : Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.Viscosity: Not available.Volatility: Not available.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability: The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials : Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Ethanediol	LD50 Oral	Rat	4700 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Ethanediol	Eyes - Mild irritant Eyes - Mild irritant Eyes - Moderate irritant Skin - Mild irritant	Rabbit Rabbit Rabbit Rabbit	-	24 hours 500 mg 1 hours 100 mg 6 hours 1440 mg 555 mg	- - -

BUY ONLINE

FREE CATALOG

SAVE UP TO 25%

AMSOIL Heavy Duty Antifreeze/Coolant

ANTHD

Sensitization

There is no data available.

Carcinogenicity

There is no data available.

Specific target organ toxicity (single exposure)

There is no data available.

Specific target organ toxicity (repeated exposure)

Name	Category	Target organs
Organic acids and other Proprietary Inhibitors	Category 2	Not determined

Aspiration hazard

There is no data available.

Information on the likely

routes of exposure

: Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.

Skin contact : Causes skin irritation.
Ingestion : Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: Adverse symptoms may include the following:

pain or irritation watering redness

Inhalation : No known significant effects or critical hazards.

Skin contact: Adverse symptoms may include the following:

irritation redness

Ingestion: No known significant effects or critical hazards.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : No known significant effects or critical hazards.

effects

Potential delayed effects: No known significant effects or critical hazards.

Long term exposure

Potential immediate : No known significant effects or critical hazards.

effects

Potential delayed effects: No known significant effects or critical hazards.

Potential chronic health effects

General: May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity : No known significant effects or critical hazards.Mutagenicity : No known significant effects or critical hazards.

AMSOIL Heavy Duty Antifreeze/Coolant

ANTHD

Teratogenicity : No known significant effects or critical hazards.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	1100.1 mg/kg

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Ethanediol	Acute LC50 6900000 μg/l Fresh water	Crustaceans - Ceriodaphnia dubia - Neonate	48 hours
	Acute LC50 41000000 μg/l Fresh water Acute LC50 8050000 μg/l Fresh water	Daphnia - Daphnia magna - Neonate Fish - Pimephales promelas	48 hours 96 hours

Persistence and degradability

There is no data available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Ethanediol	-1.36	-	low

Mobility in soil

Soil/water partition coefficient (Koc)

: There is no data available.

Mobility

: There is no data available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned

or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT	TDG	IMDG	IATA
UN number	UN3082	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Ethanediol) RQ (Ethanediol)	-	-	-
Transport hazard class(es)	9	-		-
Packing group	III	-	-	-
Environmental hazards	Yes.	No.	No.	No.
Additional information	Non-bulk packages of this product are not regulated as hazardous materials in package sizes less than the product reportable quantity, unless transported by inland waterway. The marine pollutant mark is not required when transported on inland waterways in sizes of ≤5 L or ≤5 kg. Reportable quantity 10000 lbs / 4540 kg [1136.8 gal / 4303.3 L] Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements. Remarks Limited quantity	-		-

AERG : 171

DOT-RQ Details 5000 lbs / 2270 kg [540.24 gal / 2045 L] : Ethanediol

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

> 10/12 : 11/01/2016 **Date of issue**

FREE CATALOG

SAVE UP TO 25%

AMSOIL Heavy Duty Antifreeze/Coolant

ANTHD

Transport in bulk according : Not available. to Annex II of MARPOL and

the IBC Code

Section 15. Regulatory information

U.S. Federal regulations : United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 311: Acetaldehyde

Clean Air Act Section 112

(b) Hazardous Air **Pollutants (HAPs)** : Listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

DEA List I Chemicals

: Not listed

(Precursor Chemicals)

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Immediate (acute) health hazard Delayed (chronic) health hazard

Composition/information on ingredients

Name	hazard	Sudden release of pressure		Immediate (acute) health hazard	Delayed (chronic) health hazard
	No. No.	-	No. No.	Yes. Yes.	No. Yes.

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Ethanediol	107-21-1	40 - 60
Supplier notification	Ethanediol	107-21-1	40 - 60

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: Ethanediol

FREE CATALOG

SAVE UP TO 25%

AMSOIL Heavy Duty Antifreeze/Coolant

ANTHD

New York: The following components are listed: EthanediolNew Jersey: The following components are listed: EthanediolPennsylvania: The following components are listed: Ethanediol

California Prop. 65

WARNING: This product contains less than 0.1% of a chemical known to the State of California to cause cancer. **WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	Cancer	•		Maximum acceptable dosage level
Ethanediol 1,4-Dioxane Acetaldehyde	Yes.	No.	No. Yes. 90 μg/day (inhalation)	No. No. No.

Canada

Canadian lists

Canadian NPRI : The following components are listed: Ethanediol

CEPA Toxic substances : None of the components are listed.Canada inventory : All components are listed or exempted.

Section 16. Other information

History

Date of issue mm/dd/yyyy : 11/01/2016 Date of previous issue : 02/15/2015

Version : 2

Prepared by : AMSOIL INC.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.